



MAX. PRESSURE - 65" H₂O (60Hz), 50" H₂O (50Hz)
 MAX. AIR FLOW - 160 CFM (60Hz), 133 CFM (50Hz)

MOTOR ENCLOSURE: TEFC
 HP/kw: 60Hz 2.5/1.9
 50Hz 1.5/1.1

VOLTAGE: 60Hz 115/208-230-1
 50Hz 110/220-240-1
 AMPS: 60Hz 23.6/12.9-11.8
 50Hz 17.6/8.8-9.5

STARTING AMPS: 60Hz 76 @ 230V
 50Hz
 INSULATION CLASS: B
 CONSULT FACTORY

RECOMMENDED NEMA STARTER SIZE: 1/0
 NET WEIGHT (lbs/kg): 76/34.5

REV.	DATE	REVISION	BY
		FINISH REQUIRED	

TOLERANCES UNLESS OTHERWISE NOTED
 ±.005 .000
 ±.015 .00
 FRACTIONAL
 ±1/64
 ANGULAR
 ±1°

QAC CONVERTER ACCESSORY CORP. WIND GAP, PA

TITLE: MODEL #500G REGENERATIVE BLOWER
 DRAWN BY: MJT SCALE: 1/8" = 1"
 DATE: 1-21-05
 DWG. NO.: 20222-55 DISK FILE: MEPROJ

CUSTOMER: CUSTOMER SO#: DATE:

THESE DRAWINGS AND SPECIFICATIONS CONTAIN INFORMATION PROPRIETARY AND CONFIDENTIAL TO QAC. NO PORTION OF THIS DRAWING MAY BE REPRODUCED OR COPIED WITHOUT PRIOR WRITTEN PERMISSION OF CONVERTER ACCESSORY CORPORATION.