

DUCT LENGTHS			
	DIAMETER	LENGTH	# SWEEPS
INTAKE (A)			
INTAKE (B)			
INTAKE (C)			
DISCHARGE (D)			

BLOWER MOTOR STARTER  
 INCLUDED  QUOTED OPTIONAL  NONE

DISCHARGE DUCT CLAMP \_\_\_\_\_ Ø  
 QUANTITY: \_\_\_\_\_

VENTURI:  FX2  
 FX3

Y CONNECTOR \_\_\_\_\_ Ø

INTAKE DUCT CLAMP \_\_\_\_\_ Ø  
 QUANTITY: \_\_\_\_\_

\_\_\_\_\_ Ø STANDARD  
 PICKUP NOZZLE  
 TRUMPET TYPE

TRIM ENTERS  
 (SUCTION)

TRIM DISCHARGE  
 (PRESSURE)

COLLECTION METHOD  
 36 X 72 X 48  
 EXPANDED METAL BIN  
 (SHOWN)  
 30 X 72 MESH BAG  
 60 X 144 MESH BAG  
 INCLUDED  
 QUOTED OPTIONAL  
 NONE

\_\_\_\_\_ HP REGENERATIVE BLOWER

FOX RUNNER CART - WELDED STEEL FRAME  
 SIZE: 24W X 33H X 40L

CUSTOMER: \_\_\_\_\_  
 APPROVED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

TRIM REMOVAL SPECIFICATIONS:  
 CONTINUOUS TRIM:  WIDTH: \_\_\_\_\_  
 NUMBER OF TRIMS: \_\_\_\_\_  
 LOCATION: EDGES:  OTHER:   
 DESCRIBE: \_\_\_\_\_  
 PIECES  DESCRIBE: \_\_\_\_\_  
 DID YOU SEND SAMPLES?  YES  NO  
 NOTES: \_\_\_\_\_

OPERATING SPECIFICATIONS:  
 MACHINE: \_\_\_\_\_  
 MATERIAL: \_\_\_\_\_  
 THICKNESS: MIN. \_\_\_\_\_ MAX. \_\_\_\_\_  
 WIDTH: MIN. \_\_\_\_\_ MAX. \_\_\_\_\_  
 SPEED: MIN. \_\_\_\_\_ MAX. \_\_\_\_\_  
 ELECTRICAL SUPPLY:  220-275/380-480/3PH/50-60HZ  
 110-120/220-240/1PH/50-60HZ  
 OTHER: \_\_\_\_\_  
 AMPS: \_\_\_\_\_  
 EXPLOSION PROOF:  YES  NO

THESE DRAWINGS AND SPECIFICATIONS CONTAIN INFORMATION WHICH CONVERTER ACCESSORY CORPORATION CONSIDERS PROPRIETARY AND CONFIDENTIAL. NO PORTION OF THIS DRAWING MAY BE REPRODUCED OR COPIED WITHOUT PRIORWRITTEN PERMISSION OF CONVERTER ACCESSORY CORPORATION.

**CAC** CONVERTER ACCESSORY CORP.  
 WIND GAP, PA 18091  
 WWW.CONVERTERACCESSORY.COM

TITLE  
**FOX RUNNER TWO PICKUP  
 PORTABLE TRIM REMOVAL SYSTEM**

SIZE A	DWG NO 18503-211A	REV A
DATE	DRAWN MEMAST	QUOTE NO.