


NOTE:
1) MOUNT AS SHOWN,
HORIZONTAL WITH TOP CAP UP.
2) MAXIMUM LOAD CAPACITY
500 LBS EACH / 1000 LBS PER PAIR
3) BORE SIZE REQUIRED:
(Ø2.3750 MAXIMUM IN BUSHING)
4)

CUSTOMER: _____
APPROVED BY: _____ DATE: _____
OPERATING SPECIFICATIONS:
MACHINE: _____
MATERIAL: _____
THICKNESS: MIN. _____ MAX. _____
WIDTH: MIN. _____ MAX. _____
SPEED: MIN. _____ MAX. _____
TENSION: MIN. _____ MAX. _____
CORE SIZE: _____
MAXIMUM ROLL DIAMETER: _____
MAXIMUM ROLL WEIGHT: _____

PART NUMBER: 47265-14A
THESE DRAWINGS AND SPECIFICATIONS
CONTAIN INFORMATION WHICH
CONVERTER ACCESSORY CORPORATION
CONSIDERS PROPRIETARY AND
CONFIDENTIAL.
NO PORTION OF THIS DRAWING MAY
BE REPRODUCED OR COPIED WITHOUT
PRIOR WRITTEN PERMISSION OF
CONVERTER ACCESSORY CORPORATION.

 **CONVERTER ACCESSORY CORP.**
WIND GAP, PA 18091
WWW.CONVERTERACCESSORY.COM

TITLE SIMPLOK STANDARD DUTY SHAFT HOLDER WITH MOUNTED BRONZE BUSHING			
SIZE A	DWG NO 18503-316		REV A
DATE	DRAWN	FILE MEMAST	QUOTE NO.