



CUSTOMER: _____
 APPROVED BY: _____
 DATE: _____

- STANDARD DUTY-ALUMINUM CONSTRUCTION
- HEAVY DUTY-STEEL CONSTRUCTION
- ROUND BORE SIZE: _____
- SQUARE BORE SIZE: _____

OPTIONAL CORE STOP FLANGE
 NONE RIGHT SIDE LEFT SIDE

NOTES:

OPERATING SPECIFICATIONS:

MACHINE: _____
 MATERIAL: _____
 THICKNESS: MIN. _____ MAX. _____
 WIDTH: MIN. _____ MAX. _____
 SPEED: MIN. _____ MAX. _____
 TENSION: MIN. _____ MAX. _____
 CORE DIA.: _____
 CORE MATERIAL: _____
 MAX. ROLL DIA.: _____
 MAX. ROLL WEIGHT: _____
 UNWIND REWIND
 SINGLE WIDTH SLIT WIDTHS

Ø4.000" MAXIMUM THRU BORE WITHOUT BUSHING
 Ø3.750" MAXIMUM THRU BORE WITH BUSHING

THESE DRAWINGS AND SPECIFICATIONS CONTAIN INFORMATION WHICH
 CONVERTER ACCESSORY CORPORATION CONSIDERS PROPRIETARY AND CONFIDENTIAL.
 NO PORTION OF THIS DRAWING MAY BE REPRODUCED OR COPIED WITHOUT PRIOR
 WRITTEN PERMISSION OF CONVERTER ACCESSORY CORPORATION.



WIND GAP, PA 18091
 WWW.CONVERTERACCESSORY.COM

TITLE
6" COR-LOK MECHANICAL CORE CHUCK

SIZE A	DWG NO 18503-43D	REV
DATE	DRAWN MEMAST	QUOTE NO.