

2

1

DUCT LENGTHS			
	DIAMETER	LENGTH	# SWEEPS
INTAKE (A)			
INTAKE (B)			
INTAKE (C)			
DISCHARGE (D)			
MOTIVE (E)			

D

DISCHARGE DUCT CLAMP \_\_\_\_\_ Ø

QUANTITY: \_\_\_\_\_

MOUNTING BRACKET

☐ INCLUDED

☐ OPTIONAL

☐ NONE

VENTURI: ☐ FX1

☐ FX2

☐ FX3

C

Y CONNECTOR \_\_\_\_\_ Ø

A

INTAKE DUCT CLAMP \_\_\_\_\_ Ø

QUANTITY: \_\_\_\_\_

Ø STANDARD PICKUP NOZZLE TRUMPET TYPE

TRIM ENTERS (SUCTION)

B

E

MOTIVE DUCT CLAMP \_\_\_\_\_ Ø

QUANTITY: \_\_\_\_\_

HP REGENERATIVE BLOWER

1

TRIM DISCHARGE (PRESSURE)

COLLECTION METHOD

☐ 36 X 72 X 48 EXPANDED METAL BIN (SHOWN)

☐ 30 X 72 MESH BAG

☐ 60 X 144 MESH BAG

☐ QUOTED OPTIONAL

☐ INCLUDED

☐ NONE

CUSTOMER: \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

DATE: \_\_\_\_\_

TRIM REMOVAL SPECIFICATIONS:

☐ CONTINUOUS TRIM, WIDTH: \_\_\_\_\_

NUMBER OF TRIMS: \_\_\_\_\_

LOCATION: EDGES: ☐ OTHER: ☐

DESCRIBE: \_\_\_\_\_

☐ PIECES, DESCRIBE: \_\_\_\_\_

DID YOU SEND SAMPLES? ☐ YES ☐ NO

NOTES: \_\_\_\_\_

OPERATING SPECIFICATIONS:

MACHINE: \_\_\_\_\_

MATERIAL: \_\_\_\_\_

THICKNESS: MIN. \_\_\_\_\_ MAX. \_\_\_\_\_

WIDTH: MIN. \_\_\_\_\_ MAX. \_\_\_\_\_

SPEED: MIN. \_\_\_\_\_ MAX. \_\_\_\_\_

ELECTRICAL SUPPLY: ☐ 220-275/380-480/3Ph/50-60Hz

☐ 110-120/220-240/1Ph/50-60Hz

OTHER: \_\_\_\_\_

AMPS: \_\_\_\_\_

EXPLOSION PROOF: ☐ YES ☐ NO

THESE DRAWINGS AND SPECIFICATIONS CONTAIN INFORMATION WHICH CONVERTER ACCESSORY CORPORATION CONSIDERS PROPRIETARY AND CONFIDENTIAL. NO PORTION OF THIS DRAWING MAY BE REPRODUCED OR COPIED WITHOUT PRIORWRITTEN PERMISSION OF CONVERTER ACCESSORY CORPORATION.

CAC

CONVERTER ACCESSORY CORP.

WIND GAP, PA 18091

WWW.CONVERTERACCESSORY.COM

TITLE

FOX TRIM REMOVAL SYSTEM WITH (2) PICKUPS

SIZE

A

DWG NO

18503-50D

REV

D

DATE

DRAWN

FILE

MEMAST

QUOTE NO.