

OPTIONAL Y CONNECTOR FOR SINGLE DISCHARGE
YES NO SIZE: X X

DISCHARGE DUCT CLAMP Ø QUANTITY:

DISCHARGE DUCT CLAMP Ø QUANTITY:

MOUNTING BRACKET
 INCLUDED
 OPTIONAL
 NONE

VENTURI FX1
 FX2
 FX3

MOTIVE DUCT CLAMP Ø QUANTITY:

INTAKE DUCT CLAMP Ø QUANTITY:

Ø STANDARD PICKUP NOZZLE TRUMPET TYPE

TRIM ENTERS (SUCTION)

Y CONNECTOR Ø

HP REGENERATIVE BLOWER

DISCHARGE DUCT CLAMP Ø QUANTITY:

TRIM DISCHARGE (PRESSURE)

COLLECTION METHOD
 36 X 72 X 48 EXPANDED METAL BIN (SHOWN)
 30 X 72 MESH BAG
 60 X 144 MESH BAG
 QUOTED OPTIONAL
 INCLUDED
 NONE

DUCT LENGTHS

	DIAMETER	LENGTH	# SWEEPS
INTAKE (A)			
INTAKE (B)			
DISCHARGE (C)			
DISCHARGE (D)			
DISCHARGE (E)			
MOTIVE (F)			
MOTIVE (G)			
MOTIVE (H)			

THESE DRAWINGS AND SPECIFICATIONS CONTAIN INFORMATION WHICH CONVERTER ACCESSORY CORPORATION CONSIDERS PROPRIETARY AND CONFIDENTIAL. NO PORTION OF THIS DRAWING MAY BE REPRODUCED OR COPIED WITHOUT PRIORWRITTEN PERMISSION OF CONVERTER ACCESSORY CORPORATION.

CAC CONVERTER ACCESSORY CORP.

WIND GAP, PA 18091
WWW.CONVERTERACCESSORY.COM

TITLE
FOX TRIMAWAY
DUAL VENTURI SYSTEM

SIZE A	DWG NO 18503-53C	REV C
DATE	DRAWN MEMAST	FILE QUOTE NO.

CUSTOMER: _____ DATE: _____

APPROVED BY: _____

TRIM REMOVAL SPECIFICATIONS:
 CONTINUOUS TRIM, WIDTH: _____

OPERATING SPECIFICATIONS:
MACHINE: _____
MATERIAL: _____
THICKNESS: MIN. _____ MAX. _____
WIDTH: MIN. _____ MAX. _____
SPEED: MIN. _____ MAX. _____

NUMBER OF TRIMS: _____
LOCATION: EDGES: OTHER:
DESCRIBE: _____
 PIECES, DESCRIBE: _____
DID YOU SEND SAMPLES? YES NO
NOTES: _____
OTHER: _____
AMPS: _____
EXPLOSION PROOF: YES NO

ELECTRICAL SUPPLY: 220-275/380-480/3Ph/50-60Hz
 110-120/220-240/1Ph/50-60Hz